

CLAIR LIGHTING

LED MULTI PAR RGBALC IP65

Rated voltage: AC100-240V, 50/60 Hz adaptive power supply

Rated power: 350W

Light source: 1 × 350W RGBALC

Average lifespan: 20,000 hours

Color temperature: 2000K-10000K, adjustable color temperature

CRI: 95 @ 2800K

Luminous brightness: 10215 lumens

Beam angle: 55 °

Full lamp group diffuse angle: 87 °

Color mixing system: Unified RGBALC color matching system, RGBALC infinite color mixing, extraordinary color mixing function, pure color, color macro effect, with dyeing, beam, special effects, built-in rich effect programs, etc

Strobe: 1~25 Hz fast electronic strobe

Refresh rate: 800-25K Hz

(800Hz, 1200Hz, 2000Hz, 3600Hz, 12kHz, 25kHz)

Dimming: 0-100% linear dimming mode

Dimming delay: three types

Dimming curve: four types

splicing for shaping

Protection function: Light source overheating protection, real-time temperature monitoring, ensuring the service life of the lamp

Connection method: DMX512 input/output/power input/output

Control mode: DMX512, auto, master-slave, sound, RDM

Channel mode: 1//2/3/4/6/7/13/21/10/15CH

Power interface: Waterproof True one connector, input/output

Signal interface: Waterproof XLR signal socket, input/output

Control panel: OLED display screen+4 touch buttons, supporting different Language

Software upgrade: Update software through DMX connection

Cooling method: Aluminum alloy material for heat dissipation

Waterproof rating: IP65

Product size: 216 x 213 x 151mm (L * W * H)

Net weight: 2.35KG



Multiple setup configuration of par lights