

CLAIR LIGHTING STUDIO FLOOD LIGHT

PRODUCT INTRODUCTION: This CLAIR LIGHTING STUDIO FLOOD LIGHT is made from cast-aluminium and is suitable for indoor use.

This product is made according to CE standard and is using DMX standard protocol, as well as manual control. It is suitable to use on large-scale theatres, studios and other places.

Function		
1	DMX-Addr 001	Under the current main menu, press the confirmation key to enter the adjustment state, press the upper and lower keys to adjust the address code, then press the confirmation key to save and exit the adjustment state
2	Rotar cw-ADJ	Under the current main menu, press the confirmation key to enter the drop-down menu and adjust the dimming knob to adjust the brightness of the light. Press the monkey to return to the upper menu.
3	Rotar ww-ADJ	Under the current main menu, press the confirmation key to enter the drop-down menu and adjust the dimming knob to adjust the brightness of the light. press the menu key to return to the upper menu.
4	Key-ADJ	Under the current main menu, press the confirmation key to enter the drop-down menu and press the up and down keys to adjust the brightness of the lights. Press the menu key to return to the upper menu.
5	Screen Rotate	Press the confirmation key under the current main menu. to enter the drop-down menu press the up and down keys to adjust brightness of the light. Press the menu key to return to the upper menu. Enter the selection state , press the upper and lower keys to select, determine the key to save and exit, press the menu key to return to upper menu.
Display Window Description		
1	WW-SELECT	0-255
2	RT-SELECT	0-255
3	Fan temp	20-70
4	Lowpower temp	35-90
5	Protec temp	ON/OFF
6	CW-GLO	20-255
7	WW-GLO	20-255
8	Language	EN
9	Screen saver	ON/OFF
DMX 512 Channel Description		
Ch1	Dimming	Total dimming, linear dimming from dark to light
Ch2	Strobe	Total strobe, from slow to fast
Ch3	Cat 3000-6000K	CCT 3000-6000K 0-255
RDM Description		
1	Feedback (Address Code)	Free to change
2	Feedback (Equipment temperature)	Unmodifiable
SPECIFICATION:		FEATURES:
Voltage: AC100-240 50~60Hz		- Smooth dimming adjustment, no flicker
Power: 150Watts		- Has built-in temperature sensor that automatically adjust the light amount according to temperature to prevent overheating
Beam Angle: 120°		- Uses a reflective cup to project a uniform flare
IP Rating: IP25		- Self-waking program
Dimmer: 0-100%		- With RDM function
Colour: White and Warm White		
Working Temperature: 15°C - 40°C		
DMX Channel: 3Channel		
Dimension:		
Weight: 7.2Kg		